


Channel Reveal

Surface application

Create 1/4" to 2" reveals in drywall surfaces. No backing or blocking needed. Factory fabricated intersections available.

Product Data & Ordering Information:

Product code	Board thickness	Reveal	Flanges	Length	Pcs/Box
DC50-25S	1/2"	1/4"	1-1/8"	10'	20
DC50-38S	1/2"	3/8"	1-1/8"	10'	20
DC50-50S	1/2"	1/2"	1-1/8"	10'	20
DC50-75S	1/2"	3/4"	1-1/8"	10'	15
DC50-100S	1/2"	1"	1-1/8"	10'	15
DC50-150S	1/2"	1-1/2"	1-1/8"	10'	15 or 10
DC50-200S	1/2"	2"	1-1/8"	10'	10
DC58-25S	5/8"	1/4"	1-1/8"	10'	20 or 15
DC58-38S	5/8"	3/8"	1-1/8"	10'	20 or 15
DC58-50S	5/8"	1/2"	1-1/8"	10'	15
DC58-75S	5/8"	3/4"	1-1/8"	10'	15
DC58-100S	5/8"	1"	1-1/8"	10'	12
DC58-150S	5/8"	1-1/2"	1-1/8"	10'	10
DC58-200S	5/8"	2"	1-1/8"	10'	10



Code Approvals & Performance Standards

- [ASTM C840](#) Standard Specification for Application and Finishing of Gypsum Board
- [ASTM C1047](#) Standard Specification for Accessories for Gypsum Wallboard and Gypsum Veneer Base
- [ASTM D3678](#) Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) Interior - Profile Extrusions
- [SDS Vinyl Corp](#) PVC Compounds

Storage:

All stored materials shall be kept dry. Materials shall be stacked off the ground, supported on a level platform, and protected from the weather.

