

HomeGuard™ HOUSEWRAP

Protecting you from the harsh elements of Mother Nature, HomeGuard™ housewrap excels in air and water resistance, moisture vapor permeability and durability. HomeGuard housewrap is an engineered, woven, polyolefin material designed for use as a secondary weather resistive barrier. The strong woven fabric ensures jobsite durability, even in the harshest conditions. HomeGuard's micro-perforations allow damaging moisture as a vapor to escape while shedding bulk water.



HomeGuard is designed to protect commercial and residential buildings from Mother Nature by excelling in four crucial areas:



Air Resistance - Protects the wall assembly from air infiltration to increase the comfort of the building by reducing drafts and increasing energy efficiency.



Moisture Vapor Permeability - Preserves the integrity of the wall assembly by allowing the moisture as vapor to escape to the outside.



Water Resistance - Protects the wall assembly against water intrusion that gets behind the exterior cladding.



Durability - Has the ability to withstand the elements of the weather and tough jobsite conditions.

Test	Method	Units	HomeGuard	Minimum Requirement
Tensile Strength				
Machine Direction	ASTM D 882	lbs.	54 lbs.	20 lbs.
Cross Direction	ASTM D 882	lbs.	36 lbs.	20 lbs.
Water Resistance	ASTM D 779	Minutes	60 Minutes	10 Minutes
Water-vapor Transmission	ASTM E 96	Perms	15 Perms	5 Perms
Low Temperature Bend	AC38 Section 3.3.4	N/A	Pass	Pass
UV Exposure	AC38 Section 4.1.2	N/A	6 Months	120 Days

Build your business with **Custom Imprinting** on HomeGuard™ Housewrap



- Imprint your company logo - only one pallet minimum
- Largest exposure area - 40" x 30"
- Many colors are available
- Short lead times - 3 to 4 weeks on initial order, 2 weeks on reorders
- Logo repeats every 48" in center lane

Available on 9' and 10' wide material

Putting it all together!

Using HomeGuard Housewrap is a great first step in protecting your home or project from Mother Nature's harsh elements. Help protect windows, doors and other critical areas from damaging moisture by using high quality HomeGuard Butyl Flashing and HomeGuard Seam Tape. Assure peace of mind when you use the HomeGuard System.

HomeGuard Butyl Flashing is a high-density polyethylene facer, coated with an extremely aggressive self-sealing butyl adhesive for use on window heads and jambs.

HomeGuard Seam Tape is a high-density polyethylene facer coated with an acrylic adhesive designed for sealing housewrap seams.


HomeGuard Housewrap Roll Sizes and Quantities

3' x 100' - 234 rolls
3' x 150' - 165 rolls
3' x 195' - 120 rolls

4.5' x 100' - 156 rolls
4.5' x 150' - 110 rolls
4.5' x 195' - 80 rolls

9' x 100' - 78 rolls
9' x 150' - 55 rolls
9' x 195' - 40 rolls

10' x 100' - 78 rolls
10' x 150' - 55 rolls
10' x 195' - 40 rolls



Manufactured by



EPAC INC.
FLEXIBLE PACKAGING

www.Epak.ca
1-800-665-8083



CCMC 13424-R



HomeGuard